Declassified in Part - Sanitized Copy Approved for Release 2012/02/13: CIA-RDP78-03424A001200080002-0

Office Memorandum • United States Government

	The Files - Contract 111-13224-9 DATE: 31 December 1959 REP DAYE 020550 BY 0/0956	
гом	ONIG COMP SOLUTION OF THE SOLU	25X
вјест:	Trip Report - Delivery of Propane Burning Thermoelectric Generator	
	1. On 22 December 1959 a trip was made to	25X
	electric generator. Present for discussions were:	25 X
		25X
	ing a heating source of burning propane gas. The thermoelectric elements are cylindrical ingots of lead telluride material doped to produce N and P type semi-conductors. One N and one P type element constitute a couple and the 99 couples are connected electrically in series. A propane burning radiant-type burner is used as the heat-	
	ing source and metal fins are used to control the cold side termperature. The open circuit voltage of the BC-13, when operated with a hot junction temperature of 1100°F and a cold temperature of 160°F, is 26 volts DC. The voltage across a matched load is 13.3 volts DC with a load current of 635 ma. The BC-13 has a power to fuel ratio of 208 watt hours per pound of fuel giving a net efficiency of 3.3%. The generator, including base, stand, weatherproofing material, and fins, weighs approximately 22 lbs., excluding the fuel. The BC-13 will operate approximately 15 to 20 hours on a pound of propane gas. 3. were given our requirement for	25>
	ture. The open circuit voltage of the BC-13, when operated with a hot junction temperature of 1100°F and a cold temperature of 160°F, is 26 volts DC. The voltage across a matched load is 13.3 volts DC with a load current of 635 ms. The BC-13 has a power to fuel ratio of 208 watt hours per pound of fuel giving a net efficiency of 3.3%. The generator, including base, stand, weatherproofing material, and fins, weighs approximately 22 lbs., excluding the fuel. The BC-13 will operate approximately 15 to 20 hours on a pound of propane gas.	25)
	ture. The open circuit voltage of the BC-13, when operated with a hot junction temperature of 1100°F and a cold temperature of 160°F, is 26 volts DC. The voltage across a matched load is 13.3 volts DC with a load current of 635 ma. The BC-13 has a power to fuel ratio of 208 watt hours per pound of fuel giving a net efficiency of 3.3%. The generator, including base, stand, weatherproofing material, and fins, weighs approximately 22 lbs., excluding the fuel. The BC-13 will operate approximately 15 to 20 hours on a pound of propane gas. 3.	25) 25) 25) 25)

R+D Subject
R+D Lab
OC-T
OC-SP/AF
Monthly (2)
EP Chrono

CONFIDENTIAL

CORF.